


REV	ECN	DESCRIPTION	DATE	DR	CK
A	143	ADD FM APPRVL, "L" TOLERANCES	02/05/79		LOC
B	8102	REDRAW	08/10/12	PF	MG



TEMPERATURE RANGE	OUTPUT VOLTAGE PEAK TO PEAK	DC RESISTANCE OHMS	INDUCTANCE MILLIHENRYS	OUTPUT CONNECTOR	INSULATION RESISTANCE	NET WEIGHT
-65 ° F to +225 ° F	18-23 VOLTS (SEE NOTE 1) 13V TYP AT 100 IPS	170-210 AT 75 ° F	12-16 AT 1 KHz	MATES WITH MS3106A-10SL-4S (SEE NOTE 2)	100 MEGOHMS MIN. AT 500 VDC, COIL TO HOUSING	1.9 OZ. AVG.


NOTES:

- TESTED AT 1000 INCHES/SECOND WITH A 8 PITCH, 12 TOOTH GEAR, 0.005" CLEARANCE AND 100,000 OHMS LOAD SHUNTED BY 250 MMF.
- WITH APPROACH OF FERROUS METAL, PIN "B" IS POSITIVE WITH RESPECT TO PIN "A".

CONSTRUCTION:

HOUSING ----- 303 STAINLESS STEEL
 POLE PIECE - 416 STAINLESS STEEL
 POTTING ----- EPOXY RESIN

LIMITED OUTPUT CURRENT AND VOLTAGE



THIRD ANGLE PROJECTION		Sheet 1 of 1	
DYNALCO			
MODEL	M134	DRAWN	PF
PATH	MPROD\PICKUPS\M134	APPROVED	HM
TITLE MAGNETIC PICKUP, MODEL M134			
DATE	04/10/78	A	800-0134
			REV A

TOLERANCES	FRACT.	DEC.	ANGLES
	±1/64	.XXX±.005	±1/2°
		.XX±.01	
MATERIAL			
FINISH			

THIS DOCUMENT, ALL INFORMATION CONTAINED IN AND ALL INFORMATION RELATED TO IS PROPERTY OF DYNALCO CONTROLS. IS CONFIDENTIAL TO IT AND NO PART THEREOF NOR ANY SUBSTANTIAL INFORMATION MAY BE COPIED, DISSEMINATED OR USED IN ANY MANNER WHATSOEVER WITHOUT THE WRITTEN CONSENT OF DYNALCO AND IS TO BE RETURNED TO DYNALCO UPON REQUEST.