



REV	ECN	DESCRIPTION	DATE	DR	CK
A	7866	REDRAW IN CAD	03/15/12	PF	MG



TEMPERATURE RANGE	OUTPUT VOLTAGE PEAK TO PEAK	DC RESISTANCE OHMS	INDUCTANCE MILLIHENRYS	OUTPUT CONNECTOR	INSULATION RESISTANCE	NET WEIGHT
-65 ° F to +225 ° F	260-340 VOLTS (SEE NOTE 1)	2000-2300 AT 75 ° F	850 NOM	MATES WITH MS3106A-10SL-4S (SEE NOTE 2)	100 MEGOHMS MIN. AT 500 VDC, COIL TO HOUSING	1.8 OZ. AVG.

**NOTES:**

- TESTED AT 1000 INCHES/SECOND WITH A 20 PITCH, 30 TOOTH GEAR, 0.005" CLEARANCE AND 100,000 OHM LOAD SHUNTED BY 250 MMF.
- WITH APPROACH OF FERROUS METAL, PIN "B" IS POSITIVE WITH RESPECT TO PIN "A".


**CONSTRUCTION:**

HOUSING ----- 303 STAINLESS STEEL  
 POLE PIECE --- 416 STAINLESS STEEL  
 POTTING ----- EPOXY RESIN

TOLERANCES	ANGLES
FRACT. DEC.	±1/2°
±1/64 .XXX±.005	XX±.01

MATERIAL

FINISH



THIRD ANGLE PROJECTION

Sheet 1 of 1

**DYNALCO**

MODEL M155 DRAWN PF SCALE

PATH MPROD\PICKUPS\M155 APPROVED LOC NONE

TITLE MAGNETIC PICKUP, MODEL M155

DATE 08/14/79 A 800-0155 REV A

THIS DOCUMENT, ALL INFORMATION CONTAINED IN AND ALL INFORMATION RELATED TO THE PROPERTY OF DYNALCO CONTROLS, IS CONFIDENTIAL TO IT AND NO PART THEREOF NOR ANY SUBSTANTIAL INFORMATION MAY BE COPIED, DISSEMINATED OR USED IN ANY MANNER WHATSOEVER WITHOUT THE PRIOR WRITTEN CONSENT OF DYNALCO AND IS TO BE RETURNED TO DYNALCO UPON REQUEST.